CONCEALED HINGE

25 mm Overlay

Overlay 21 - 25 mm (When Bore Distance is 8 mm) Cup Dia Φ 40 Bore Depth 15 mm Door Thickness 18 - 30 mm

Mounting Plate J95-P6T (P.368)



Picture above is the combination of concealed hinge and mounting plate.

CONCEALED HINGE

J95


Item Code	Item Name	Туре	Material	Finish	Weight Carton
160-026-905	J95-24/25T	w/o Catch	Body/Steel,	Niekol	131 g 100 pcs 143 g 100 pcs
160-026-731	J95-C24/25T	w/ Catch	Cup/Zinc	MICKEI	143 g 100 pcs
160-034-919	J95-24/25T BN	w/o Catch	Alloy (ZDC)	Black	134 g 100 pcs
160-034-916	J95-C24/25T BN	w/ Catch	Alloy (ZDC)	Nickel	146 g 100 pcs

Features

- 3-way-adjustment function by mounting plate (depth + 1.5, 2.5 mm, vertical ± 3 mm, overlay [horizontal] + 0, - 4 mm).
- Snap on mount.

Sold Separately

- Mounting plate (P.368)
- Face plate for glass door (P.373)
- Safety cover (P.373)
- Cover for mounting plate (P.373)



Bore Distance (C)

Bore Distance (C)	3	4	5	6	7	8
Overlay (E)	20	21	22	23	24	25

Overlay adjustment (- 4 mm) by turning the overlay adjustment screw.

Opening Clearance (O.C.)

Clearances for door edge O.C. (A) and hinge side O.C. (B) are necessary. O.C. (A) and (B) change depending on door thickness and bore distance (C). Refer to locus chart and tables below when designing cabinets.

O.C. (B)


Door		В	Bore Distance (C)					
Thickness (D)	3	4	5	6	7	8		
18	0.3	0.3	0.3	0.3	0.3	0.3		
20	0.5	0.5	0.5	0.5	0.5	0.5		
22	0.8	0.8	0.8	0.7	0.7	0.7		
24	1.1	1.1	1.1	1.1	1.1	1.0		
26	1.7	1.6	1.6	1.5	1.5	1.5		
28	3.2	2.8	2.5	2.2	2.1	2.0		
30	5.0	4.5	4.0	3.6	3.3	3.0		
32	6.8	6.2	5.7	5.2	4.8	4.4		
34	8.6	8.0	7.5	6.9	6.5	6.0		
	O.C. (B)							

Please refer to the locus chart if door thickness is over 30 mm.

O.C. (A)

	Door Thickness (D) 30	Door Width							
		300	400	500	600	700	800	900	
		0.50	0.30	0.30	0.20	0.20	0.20	0.20	
		O.C. (A)							

Cut Out Dimensions



Recommended screw

Size 5 raised countersunk head tapping screw or wood screw.

Door Dimensions and Number of Hinges

Please refer to P.368.

